

# Product Environmental Profile



## SIRCOVER (I-0-II)

*SIRCOVER products are manually operated transfer switches with positive break indication.*

*3 & 4 poles versions for open transition switching (I-0-II)*



### The commitments of Socomec to respect the environment

As part of its environmental policy, Socomec is committed to:

- Incorporate the principles of the circular economy into the design of new products and services
- Promote longer product lifetimes
- Promote the use of environmentally responsible materials
- Design and develop solutions to further improve the energy efficiency of our products and services
- Inform our customers in a transparent manner about the environmental impact of our products throughout their life cycle.

To this end, Socomec is committed to constantly monitoring, anticipating and complying with environmental regulations as well as customer expectations relating to its products, and to ensuring that all those involved adhere to and take responsibility for its commitments.

Socomec is member of :



Member of WEEE Europe



Environment and sustainable development commissions



PEP ecopassport® Registration number: SOCO-00074-V01.01-EN

SOCOMECS.A.S

Head office : 1, rue de Westhouse – F – B.P.60010 – 67235 Benfeld Cedex

Tél : 03 88 57 41 41 – Fax : 03 88 57 78 78 – [www.socomec.com](http://www.socomec.com)

Contact : [http://www.socomec.com/contact-us\\_en.html](http://www.socomec.com/contact-us_en.html)

## ● Product information :

### Reference product

The representative product is the SIRCOVER 4X630A F with sales reference 41AC4063 with the following description: SIRCOVER products are manually operated transfer switches with positive break indication.

### Other covered references

This PEP covers other references listed in the table at the end of the document.

### Functional unit

Ensure continuity of energy supply by transferring a load between two power supply sources for rated current from 125A to 3200A and rated voltage of 415VAC, for enclosure installation, in industrial applications areas, according to the appropriate use scenario, and during the reference life of 20 years of the product.

## ● Materials and substances

### Declaration of the constitutives materials

Total mass of the reference product (including packaging): 14,7 kg among which packaging: 1,12 kg

For the reference product:

Plastics as % of weight		Metals as % of weight		Other as % of weight	
Polyester	44,04%	Copper and its alloys	19,39%	Cardboard	7,39%
Polyamide	0,57%	Steel	14,42%	Paper	0,60%
		Stainless steel	7,62%	Other organics	<0,1%
		Zamak	5,95%		
		Zinc and its alloys	<0,1%		
		Precious metals	<0,1%		
Other plastics	<0,1%				
<b>Total Plastics: 6,28 kg</b>	<b>44,62%</b>	<b>Total Metals: 6,67 kg</b>	<b>47,39%</b>	<b>Total Others: 1,12 kg</b>	<b>7,99%</b>

### Substances management

Socomec is leading a program to limit the use of hazardous substances in the design of new products and to monitor the presence of substances of concern in its supplies to anticipate future use restrictions.



Directive 2011/65/EU : Product references covered by this PEP meet the requirements of the RoHS Directive on the restriction of substances such as lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), polybrominated diphenyl ethers (PBDEs) and phthalates (DIBP, DEHP, BBP, DBP).



REACH 1907/2006 regulation: To the best of our knowledge, based on the supplier declarations, at the publication date of this document, the product do not contain any other SVHC in a concentration above 0,1% per weight.

## • Manufacturing



The products covered by this PEP are manufactured on the production site of Benfeld, France whose environmental management system has been ISO 14001 certified. Impacts on the environment are reduced by optimizing its energy consumption and by practicing a rigorous waste management

## • Distribution

As part of its distribution policy aiming to respect the environment, Socomec is in favor of groupage transports and ISO 14001 certified logistic partners.

No reconditioning is planned for the product. This phase is consequently neglected.

The sizing of the packaging has been optimized to ensure the best possible protection of the product at the lowest possible volume in order to reduce the impact of the transport stage on the environment.

## • Installation

The installation phase consists in connecting the product to the existing electrical installation.

The installation does not generate any significant impacts on the environment, except impacts from packaging waste.

## • Use phase

Use phase was modelised according to the following scenario:

Geography: European energy mix

Load rate: 50% of 630A (In)

Use time rate: 15% of the time over 20 years (RLT) according to IEC TS 63058

## Care and maintenance

The product does not require any maintenance under normal conditions of use.

## Consumables

The product does not require consumables.

## ● End of life

### End of life treatment

SIRCOVER references covered by this PEP do not contain hazardous components as defined in Annex VII of the WEEE Directive 2012/19/EU - Waste of electrical and electronic equipment.

Maintenance and disassembly should always be conducted by qualified personnel.

### Recovery potential of the product according to IEC TR 62635

The recovery potential of the product is 49,9%.

This covers material and energy recovery potentials.

## ● Environmental impacts

### Calculation methodology: life cycle assessment (LCA)



The calculation of the impacts on the environment was made using a life cycle assessment methodology in accordance with the ISO 14040 requirements and with PEP eco passport product category rules. For more details follow the link:

[www.pep-ecopassport.org](http://www.pep-ecopassport.org)

This study was carried out with the following version of the software EIME and of the database:

EIME version: 6.0.4

Database version: CODDE-2023-02

For biogenic carbon storage the following methodology was used : 0/0

The whole life cycle has been taken into account:

Step	Geographical representativeness	Scenario
<b>Manufacturing (M) (A1-A3)</b>	Production of other components and packaging : Europe Assembly : France	From the raw material extraction to the last Socomec logistic platform, including packaging Waste generated during manufacturing phase are taken into account.
<b>Distribution (D) (A4)</b>	Distribution scenario : Europe	From the last Socomec logistic platform to the final customer.
<b>Installation (I) (A5)</b>	Transport and treatment of packaging wastes : Local	Local road transport of 1000 km of generated wastes to the treatment site, end of life treatment.
<b>Use phase (U) (B1-B7)</b>	Energy mix : Europe	Power consumption required during 20 years and maintenance according to consumption scenario above mentioned.
<b>End of life (EOL) (C1-C4)</b>	Transport and treatment : Local	Road transport of 1000 km from the final customer to the treatment sites. End of life treatment.

## Environmental impacts of the reference product, per FU

The following impacts have been calculated to best represent geographically, temporally and technologically each step of the life cycle.

Indicators	Unit	Total impact	M (A1-A3)	D (A4)	I (A5)	U (B1-B7)	EOL (C1-C4)
Acidification	mol H+ eq.	3,62E+00	1,42E+00	1,64E-02	3,73E-03	2,16E+00	1,44E-02
Climate change - Total	kg CO2 eq.	5,01E+02	1,14E+02	2,59E+00	1,35E+00	3,77E+02	5,81E+00
Climate change - Biogenic	kg CO2 eq.	3,98E+00	3,42E+00	0*	5,67E-02	5,03E-01	0*
Climate change - Fossil	kg CO2 eq.	4,97E+02	1,11E+02	2,59E+00	1,29E+00	3,77E+02	5,81E+00
Climate change - Land use and land use transformation	kg CO2 eq.	0,00E+00	0*	0*	0*	0*	0*
Ecotoxicity, freshwater	CTUe	5,59E+03	1,51E+03	1,75E+00	1,44E+01	4,06E+03	3,97E+00
Particulate matter	disease occurrence	2,56E-05	8,71E-06	1,34E-07	2,30E-08	1,67E-05	0*
Eutrophication, freshwater	kg P eq.	1,37E-03	2,12E-04	9,72E-07	1,68E-05	1,03E-03	1,05E-04
Eutrophication, marine	kg N eq.	4,13E-01	1,46E-01	7,70E-03	1,79E-03	2,47E-01	1,04E-02
Eutrophication, terrestrial	mol N eq.	5,49E+00	1,58E+00	8,44E-02	1,18E-02	3,70E+00	1,13E-01
Human toxicity, cancer	CTUh	2,68E-03	2,68E-03	0*	0*	0*	0*
Human toxicity, non-cancer	CTUh	1,66E-05	1,49E-05	4,93E-09	5,28E-09	1,74E-06	0*
Ionising radiation, human health	kBq U235 eq.	1,52E+03	9,56E+02	0*	1,83E-01	5,61E+02	1,92E-01
Land use	No dimension	1,62E+01	8,66E+00	0*	3,27E-03	7,50E+00	0*
Ozone depletion	kg CFC-11 éq.	7,95E-06	6,20E-06	3,97E-09	1,58E-08	1,61E-06	1,16E-07
Photochemical ozone formation, human health	kg NMVOC eq.	1,41E+00	5,67E-01	2,13E-02	2,76E-03	7,92E-01	2,43E-02
Abiotic resource depletion - fossil fuels or resource depletion - fossils	MJ	1,19E+04	2,29E+03	3,62E+01	1,23E+01	9,61E+03	0*
Abiotic resource depletion - elements or resource depletion - metals and minerals	kg Sb eq.	5,42E-03	5,58E-03	0*	0*	2,73E-05	0*
Water use	m³ eq.	7,02E+01	5,52E+01	9,84E-03	9,16E-02	1,33E+01	1,55E+00
Net use of freshwater	m³	1,63E+00	1,28E+00	2,29E-04	2,13E-03	3,11E-01	3,60E-02
Total Primary Energy	MJ	1,39E+04	2,39E+03	3,62E+01	1,39E+01	1,15E+04	0*
Total use of non-renewable primary energy resources	MJ	1,19E+04	2,29E+03	3,62E+01	1,23E+01	9,61E+03	0*
Total use of renewable primary energy resources	MJ	1,95E+03	1,02E+02	0*	1,55E+00	1,84E+03	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1,17E+04	2,07E+03	3,62E+01	1,23E+01	9,61E+03	0*
Use of non renewable primary energy resources used as raw material	MJ	2,24E+02	2,24E+02	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1,92E+03	7,34E+01	0*	1,55E+00	1,84E+03	0*
Use of renewable primary energy resources used as raw material	MJ	2,84E+01	2,84E+01	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of secondary material	kg	1,61E+00	1,61E+00	0*	0*	0*	0*
Hazardous waste disposed	kg	4,10E+02	4,06E+02	0*	0*	7,04E+00	0*
Non hazardous waste disposed	kg	2,06E+02	1,53E+02	9,10E-02	5,05E-01	5,43E+01	0*
Radioactive waste disposed	kg	9,11E-02	7,76E-02	6,48E-05	6,15E-05	1,14E-02	2,01E-03
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Exported Energy	MJ	0,00E+00	0*	0*	0*	0*	0*

# PRODUCT ENVIRONMENTAL PROFILE

Materials for energy recovery	kg	1,01E-01	0*	0*	1,01E-01	0*	0*
Materials for recycling	kg	0,00E+00	0*	0*	0*	0*	0*

Biogenic carbon content in the reference product:

Biogenic carbon content of the product	kg of C	0,00E+00	0*	N/A	N/A	N/A	N/A
Biogenic carbon content of the associated packaging	kg of C	3,14E-01	3,14E-01	N/A	N/A	N/A	N/A

NB : 0\* means that this impact either represents less than 0.01% of the total life cycle of the reference flow, or has no impact (in the case where the total impact is zero).

For the use stage (U), the product does not require maintenance therefore the impacts values are representatives of the B6 phase from the use stage : "Energy requirements during the use stage"

Registration number : SOCO-00074-V01.01-EN	Drafting Rules : "PEP-PCR-ed4-EN 2021 09 06" Supplemented by : "PSR-0005-ed3-EN-2023 06 06"
Verifier accreditation number : VH12	Information and reference documents : <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue: 08-2023	Validity period : 5 years
Independant verification of the declaration and data in compliance with ISO 14025 : 2006	
Internal : <input checked="" type="checkbox"/>	External : <input type="checkbox"/>
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain) PEPs are compliant with XP C08-100-1 : 2016 or EN 50693:2019 The components of the present PEP may not be compared with components from any other program.	
Document complies with ISO 14025:2006 "Environmental labels and declarations. Type III environmental declarations" <input type="checkbox"/>	



*This document is intended to be only informative and non-contractual and does not create any right or obligation or commitment for Socomec towards its associates, customers or any other person or entity. All the values indicated in this document may change depending on many factors (use conditions, applications, installations, environment...). The life time mentioned in this document is only indicative and is not intended to be the minimal, maximal or average life time of the product.*

## Other references covered and extrapolation factors

For the products covered by the PEP other than the reference product, the environmental impacts of each phase of the lifecycle may be calculated with extrapolation factors following the proportionality rules that you can find below.

Extrapolation factors are determined as follows and can be provided upon request:

- For the Manufacturing and Distribution phases they are proportional to the mass of the product with its packaging;
- For the Installation phase they are proportional to the mass of the packaging;
- For the Use phase they are proportional to the power losses of the product;
- For the End of Life phase they are proportional to the mass of the product without its packaging.

Model	Reference
SIRCOVER 4X630A F	41AC4063
SIRCOVER 3X125A F	41AC3013
SIRCOVER 4X125A F	41AC4013
SIRCOVER 3X160A F	41AC3016
SIRCOVER 4X160A F	41AC4016
SIRCOVER 3X200A F	41AC3020
SIRCOVER 4X200A F	41AC4020
SIRCOVER 3X250A F	41AC3025
SIRCOVER 4X250A F	41AC4025
SIRCOVER 3X315A F	41AC3031
SIRCOVER 4X315A F	41AC4031
SIRCOVER 3X400A F	41AC3040
SIRCOVER 4X400A F	41AC4040
SIRCOVER 3X500A F	41AC3050
SIRCOVER 4X500A F	41AC4050

Model	Reference
SIRCOVER 3X630A F	41AC3063
SIRCOVER 3X800A F	41AC3080
SIRCOVER 4X800A F	41AC4080
SIRCOVER 3X1000A F	41AC3100
SIRCOVER 4X1000A F	41AC4100
SIRCOVER 3X1250A F	41AC3120
SIRCOVER 4X1250A F	41AC4120
SIRCOVER 3X1600A F	41AC3160
SIRCOVER 4X1600A F	41AC4160
SIRCOVER 3X2000A F	41AC3200
SIRCOVER 4X2000A F	41AC4200
SIRCOVER 3X2500A F	41AC3250
SIRCOVER 4X2500A F	41AC4250
SIRCOVER 3X3200A F	41AC3320
SIRCOVER 4X3200A F	41AC4320